

Make a lasting impression.



Multiquip's Mikasa Brand Plate Compactors are recognized as the industry standard for compacting granular soils and asphalt.

# With all the features you need:

**Reliable engine** – Honda GX-160 offers easy starting and low oil shutdown for durability.

Cyclonic pre-cleaner – captures most airborne contaminants for engine protection and extended service life.

3 Single cast baseplate and eccentric housing – lower center of gravity and increases travel speed by 12% for greater productivity.

- Hour / Tachometer Measures run time and engine RPM.
- 5 **Protective frame** Tubular steel roll bar protects engine components and provides central lifting point.
- Anti-vibration handle –
  Dramatically reduces operator fatigue and increases productivity. Up to 50% less vibration than competitive designs.
- Sealed belt cover Keeps dirt and rocks out of and extends belt life.
- **Convenient oil drain** Facilitates easy access to engine oil for maintenance.
- **Cog-tooth belt drive** Enables longer life compared to conventional V-belts.
- **Removable water tank –** Easy refilling and removable without tools (largest in it's class).
- Open base plate design Makes for easier removal of dirt and rock build-up. Cast Iron construction for durability.

## **MVC88VTHW**

Weight Ib (kg) - 229 (104)

Plate size WxL in (mm) - 19.7x20.7 (500x525))

Plate - Cast iron

Tank size qt. (ltr) - 13.7 (13.0)

Cyclonic Pre-Cleaner - Dual

# **MVC88 Equipment Options:**



Wheel Kit - attaches to frame and simplifies mobility.



**Urethane plate -** attachment for use on paving stones and brick pavers.



Water Tank - removable without tools, largest in its class, and self-contained water shut-off valve.



## MVC40H

Weight lb (kg) - 110 (50)

**Plate size WxL in (mm) -** 11.61x16.53 (295x420)

Plate - Steel

Handle - Stowable



### **MVC64VHW**

Weight lb (kg) - 151(68)

**Plate size WxL in (mm) -** 13.8x21.3 (350x540)

Plate - Steel

**Tank size qt. (ltr) -** 8.8 (8.3)



### **MVC82VHW**

Weight Ib (kg) - 181(82)

**Plate size WxL in (mm) -** 17.7x22 (450x570)

Plate - Steel

Tank size qt. (ltr) - 11.5 (10.9)

Cyclonic Pre-Cleaner - Dual



## MVC90

- Tubular steel roll bar cage protects engine components and provides a lifting point
- Powered by a Honda engine with low oil alert and double V-belt drive
- Heavy-duty steel base plate closed design, ribbed for extra strength
- Integral water- distribution system with steel tank

Weight lb (kg) - 194 (88)

**Plate size WxL in (mm) -** 19.7x22 (500x560)

Plate - Steel

**Tank size qt. (ltr) -** 4 (3.8)

# **Superior Details:**



**Baseplate Design -** open for easy removal of rock build up and special contour for asphalt applications.



**Anti-Vibration Handle -** four point vibration filtration system reduces operator fatigue.



# **Plate Compactors**

# **Specifications**

Model	Plate Size WxL in. (mm)	Centrifugal Force Ibs. (kN)	Exciter Speed VPM	Max. Fwd. Speed ft./min. (m/min)	Gasoline Engine	Start Method	HP Rating BHP (kw)*	Water Tank Capacity qt. (ltr)	Operating Weight Ibs. (kg)
MVC40H	11.61x16.53 (295x420)	1,619 (7.2)	6,200	82 (25)	Honda GX-100	Recoil	2.8 (2.1)	N/A	110 (50)
MVC64VH	13.8x21.3 (350x540)	2,275 (10.1)	5,600	82 (25)	Honda GX-120	Recoil	3.5 (2.6)	N/A	151 (68)
MVC64VHW	13.8x21.3 (350x540)	2,275 (10.1)	5,600	82 (25)	Honda GX-120	Recoil	3.5 (2.6)	8.8 (8.3)	157 (71)
MVC82VH	17.7×22 (450×570)	3,080 (13.7)	5,600	72 (22)	Honda GX-160	Recoil	4.8 (3.6)	N/A	175 (79)
MVC82VHW	17.7×22 (450×570)	3,080 (13.7)	5,600	72 (22)	Honda GX-160	Recoil	4.8 (3.6)	11.5 (10.9)	181 (82)
MVC88VTH	19.7×20.7 (500×525)	3,372 (15)	6,000	82 (25)	Honda GX-160	Recoil	4.8 (3.6)	N/A	207 (95)
MVC88VTHW	19.7x20.7 (500x525)	3,372 (15)	6,000	82 (25)	Honda GX-160	Recoil	4.8 (3.6)	13.7 (13.0)	229 (104)
MVC90H	19.7×22 (500×560)	3,417 (15.2)	5,800	82 (25)	Honda GX-160	Recoil	4.8 (3.6)	4 (3.8)	194 (88)

<sup>\*</sup>Engine power ratings are calculated by the individual engine manufacturer and the rating method may vary among engine manufacturers. Multiquip Inc. and its subsidiary companies makes no claim, representation or warranty as to the power rating of the engine on this equipment and disclaims any responsibility or liability of any kind whatsoever with respect to the accuracy of the engine power rating. Users are advised to consult the engine manufacturer's owners manual and its website for specific information regarding the engine power rating.

## **Accessories:**

### **Urethane Pad Attachment**



Urethane Pad Model: UPA88T					
Plate Model	Serial Number				
MVC88VTH(W)	ALL				
MVC82VH(W)	B-3812 and above				

#### Water Tank Kit (full) **Assembly**



Plate Model	Tank		
MVC40	731099		
MVC64VHW	52677		
MVC82VWH	52693		
MVC88VGHW	52680		
MVC88VTHW	731598		



Plate Model	Wheel Kit	Serial Number		
MVC64VH(W)	WHL64	ALL		
MVC82VH(W)	WHL82	C-2073 and above		
MVC88VTH(W)	WHL88T	A-9197 and below		
MVC88VTH(W)	WHL88TC	A-9198 ~ C-1471		
MVC88VTH(VV)	WHL88T	C-1472 and above		

### **WARRANTY**

Vibratory Plate Compactors-1 year parts and labor. Contact Multiquip for complete warranty information. Honda GX Series engines - 3 years. Please consult the manufacturer for warranty details and updates.

### Your Multiquip dealer is:

Connect with us on









