

# **RGC**<sup>®</sup>

**REIMANN & GEORGER CORP.**

## **2017 CONSTRUCTION PRICE LIST**



**RGC IS THE NORTH AMERICAN DISTRIBUTOR  
FOR HYCON POWER SYSTEMS**



**AVAILABLE IN 8 GPM  
 & 12 GPM MODELS!**

**HydraCutter C150™**

**HYDRACUTTER C150™ FEATURES & BENEFITS**

- Powerful hydraulic motor (requires 8 gpm @ 2000 - 2500 psi) for the C150™-8.
- Powerful hydraulic motor (requires 12 gpm @ 2000 - 2500 psi) for the C150™-12.
- Dual function trigger starts and stops saw and water simultaneously.
- New cast aluminum ergonomic frame enhances cutting precision while reducing operator fatigue.
- Choice of two diamond segmented chains for each saw:
  1. The S-series chains cut medium-soft to very hard aggregate with moderate to heavy steel reinforcing.
  2. The L-series chains cut green concrete, brick and concrete block without steel reinforcing.
- Trigger lockout
- Choice of a 15 in., 20 in. or 30 in. tapered bar featuring a roller nose sprocket and internal water ports for maximum bar and chain life.
- 15in., 20 in., or 30in. cutting depth.

**ACCESSORIES AND TOOLS**

Part #	Description	Price
1909609	ILD™ Auxiliary Hydraulic In-Line Pump	
1914101	C150™ Cast Speedhook - 42in..	

Contact RGC for availability of these items and services:

- Saw and Power Unit Packages
- Bar Reconditioning Service

**RGC NOW SELLS MAX CUT  
 BARS & CHAINS**

~ See page 3 for Chain Application Guide ~

**HYDRACUTTER C150™**

Part #	Model	Description	Price
1914010	C150-8	C150-8 GPM w/ 15 in. Bar & 76-S or 76-L Chain	
1914012	C150-8	C150-8 GPM w/ 20 in. Bar & 88-S or 88-L Chain	
1914002	C150-12	C150-12 GPM w/ 15 in. Bar & 62-S or 62-L Chain	
1914004	C150-12	C150-12 GPM w/ 20 in. Bar & 72-S or 72-L Chain	
1914006	C150-12	C150-12 GPM w/ 30 in. Bar & 90-S or 90-L Chain	

**HYDRACUTTER C150™ - 8 GPM  
 BARS, CHAINS & PARTS**

Part #	Model	Description	Price
1927015		15 in. Bar (38 cm)	
1927020		20 in. Bar (51 cm)	
5260761	76-S	Chain for 15 in. Bar Replaces SL25-76	
5260762	76-L	Chain for 15 in. Bar Replaces SL45-76	
5260881	88-S	Chain for 20 in. Bar Replaces SL25-88	
5260882	88-L	Chain for 20 in. Bar Replaces SL45-88	
1907135		8 GPM Drive Sprocket (18 Tooth)	
5807195		Trantorque® Shaft Adapter	

**HYDRACUTTER C150™ - 12 GPM  
 BARS, CHAINS & PARTS**

Part #	Model	Description	Price
1945615		15 in. Bar (38 cm)	
1945620		20 in. Bar (51 cm)	
1945630		30 in. Bar (76 cm)	
5245601	62-S	Chain for 15 in. Bar	
5245603	62-L	Chain for 15 in. Bar	
5245611	72-S	Chain for 20 in. Bar	
5245613	72-L	Chain for 20 in. Bar	
5245621	90-S	Chain for 30 in. Bar	
5245623	90-L	Chain for 30 in. Bar	
1914801		12 GPM Drive Sprocket (15 Tooth)	
5807195		Trantorque® Shaft Adapter	



**C50 HydraCutter**

### C50 CHAINSAW FEATURES & BENEFITS

- Powerful hydraulic motor requires 8 gpm @ 2000 - 2250 psi.
- Dual-function trigger starts and stops tool and water simultaneously.
- Lightweight aluminum is ergonomically designed to enhance cutting precision while reducing operator fatigue.
- Choice of two diamond segmented chains:
  1. The S-Series chains cut medium-soft to very hard aggregate with moderate to heavy steel reinforcing
  2. The L-Series chains cut green concrete, brick and concrete block without steel reinforcing
- Trigger lockout
- Choice of a 13 in. or 15 in. bar featuring a roller nose sprocket and internal water passages for maximum bar and chain life.
- 13 in. or 15 in. cutting depth.

#1911013 C50 w/ 13 in. Bar & S or L Chain .....

#1911015 C50 w/ 15 in. Bar & S or L Chain .....

### RGC NOW SELLS MAX CUT BARS & CHAINS

~ See page 3 for Chain Application Guide ~



**Cardi Electric Chainsaw**

1-800-RGC-TOOL (742-8665)

### C50 HYDRACUTTER BARS, CHAINS & PARTS

Part #	Model	Description	Price
1911916		13 in. C50 Bar (33 cm)	
1911919		15 in. C50 Bar (38 cm)	
5260501	50-S	Chain for 13 in. C50 Bar Replaces SL25-50	
5211134	50-L	Chain for 13 in. C50 Bar Replaces SL45-50	
5260551	55-S	Chain for 15 in. C50 Bar Replaces SL25-55	
5211154	55-L	Chain for 15 in. C50 Bar Replaces SL45-55	
6711964		C50 Drive Sprocket (9 Tooth)	
5807195		Trantorque® Shaft Adapter	
1909609		ILP™ Auxiliary Hydraulic In-Line Pump	

Contact RGC for other specifications. 1.800.RGC.TOOL

### Contact RGC for availability of these items and services:

- Saw and Power Unit Packages
- Bar Reconditioning Service



**C100 HydraCutter**

– Available Spring 2017 –

### CARDI SAW FEATURES & BENEFITS

#2315220 Cardi Saw w/ Bar and Chain .....

- Designed to cut concrete and masonry.
- 220V single phase motor for indoor or outdoor use.
- Multifunction electronic clutch protects against overload.
- Built in GFCI.
- Dual insulation.
- Quiet indoor cutting.
- 15 ft. electric cord.
- 58 diamond segments.
- Soft start.
- 13 in. cutting depth.

### CARDI BAR, CHAIN & PARTS

Part #	Model	Description	Price
5291301		13 in. Cardi Bar (33 cm)	
5212581	58-S	Chain for 13 in. Cardi Bar	
5290832		Cardi Drive Sprocket (8 tooth)	
5423220		Converter Box (110V to 220V)	

**BLADES FOR CIRCULAR & RING SAWS**

ARIX™ CIRCULAR SAW BLADES		
Part #	Description	Price
5251401	14 " x 1" x .125" - concrete w/ heavy rebar	
5251402	14 " x 1" x .125" - concrete w/ std. rebar	
5251403	14 " x 1" x .125" - concrete w/ no rebar	
5251407	14 " x 1" x .125" - Construction/Rescue (diamond)	
5251601	16 " x 1" x .125" - concrete w/ heavy rebar	
5251602	16 " x 1" x .125" - concrete w/ std. rebar	
5251603	16 " x 1" x .125" - concrete w/ no rebar	
5251607	16 " x 1" x .125" - Construction/Rescue (diamond)	
5252001	20 " x 1" x .125" - concrete w/ heavy rebar	
5252002	20 " x 1" x .125" - concrete w/ std. rebar	
5252401	24 " x 1" x .125" - concrete w/ heavy rebar	
5252402	24 " x 1" x .125" - concrete w/ std. rebar	

NON-ARIX™ CIRCULAR SAW BLADES		
Part #	Description	Price
5251406	14 " x 1" x .125" - Economy blade	
5251405	14 " x 1" x .125" - Premium blade	
5251404	14 " x 1" x .125" - Pre-stressed concrete	
5251606	16 " x 1" x .125" - Economy blade	
5251605	16 " x 1" x .125" - Premium blade	
5251604	16 " x 1" x .125" - Pre-stressed concrete	
5212201	20 " x 1" x .125" - Economy blade	
5212202	20 " x 1" x .125" - Premium blade	
5212241	24 " x 1" x .125" - soft/abrasive - no rebar	
5212242	24 " x 1" x .125" - med-soft to very hard - w/ rebar	

ARIX™ RING SAW BLADES		
Part #	Description	Price
5254161	16 " 3-Groove Hycon Ring w/ Drive Wheel	
5254141	14" Husqvarna Ring - no Drive Wheel	

NON-ARIX™ RING SAW BLADES		
Part #	Description	Price
5213040	16" 3-Groove Hycon Ring w/ Drive Wheel - Hard/Rebar	
5213060	16" 3-Groove Hycon Ring w/ Drive Wheel - Soft/no Rebar	

**BARS & CHAINS FOR HYDRAULIC CHAIN SAWS**

CHAIN SAW REPLACEMENT CHAINS			
Part #	Model	Description	Price
5245701	50-L	Chain for 10 in. Bar Replacement for ICS Part #531745	
5245703	50-S	Chain for 10 in. Bar Replacement for ICS Part #531739	
5245711	57-L	Chain for 15 in. Bar Replacement for ICS Part #535343	
5245713	57-S	Chain for 15 in. Bar Replacement for ICS Part #531735	
5245721	67-L	Chain for 20 in. Bar Replacement for ICS Part #531751	
5245723	67-S	Chain for 20 in. Bar Replacement for ICS Part #531741	
5245731	79-L	Chain for 25 in. Bar Replacement for ICS Part #535346	
5245733	79-S	Chain for 25 in. Bar Replacement ICS Part #531737	

ICS 880/890 STANLEY DS12 CHAIN SAW REPLACEMENT BARS		
Part #	Description	Price
1945710	10 in. Bar - Replacement ICS Part #529829	
1945715	15 in. Bar - Replacement ICS Part #523080	
1945720	20 in. Bar - Replacement ICS Part #529767	
1945725	25 in. Bar - Replacement ICS Part #525320	

ICS CHAIN SAW DRIVE SPROCKET		
Part #	Description	Price
5291242	Drive Sprocket (12 tooth) ICS Part #525495	

**CHAIN APPLICATION GUIDE**

All diamond chains are available in two bonds:

- L-Series: Longer cutting life for abrasive, soft & medium material
- S-Series: Faster cutting speed for hard & heavy reinforced material

# 2017 HYDRASAWS, HYDRACARTS, FS20, HANDLE ATTACHMENT & SAW BLADES



S16  
HydraSaw



FS20 Flat Saw w/  
Upright Handle Kit

## HYDRASAWS & ACCESSORIES

All saws include Guard, Water Attachment for wet cutting, Hose whips w/ Flush-Face fittings and Trigger Lockout. (Hydraulic requirements: 5-8 gpm @ 2000-2500 psi.)

Part #	Model	Description	Weight	Price
2031400	TS14	14 in. circular trench saw w/ 5-1/4 in. cutting depth. 4100 rpm @ 8 gpm	39 lbs.	
2001400	S14	14 in. circular saw w/ 5-1/4 in. cutting depth. 4100 rpm @ 8 gpm	28 lbs.	
2001600	S16	16 in. circular saw w/ 6 in. cutting depth. 2750 rpm @ 8 gpm	39 lbs.	
2002000	S20	20 in. circular saw w/ 7-1/2 in. cutting depth. Auxiliary Handle kit included. 1830 rpm @ 8 gpm	52 lbs.	
2002400	S24	24 in. circular saw w/ 9-1/2 in. cutting depth. Auxiliary Handle kit included. 1455 rpm @ 8 gpm	55 lbs.	
2011460		Wall Mount HydraSaw Guide 39" Kit*	34 lbs.	
2011465		Wall Mount HydraSaw Guide 84" Kit*	44 lbs.	
2011470		Wall Mount HydraSaw Guide Door Kit*	54 lbs.	

\* Wall Mount Guide Kits are designed for use with S14, S16, S20 & S24 HydraSaws.

~ See page 3 for HydraSaw Blade Options ~



HydraCart with S24 HydraSaw

## FS20 FLAT SAW

All saws include Guard, Water Attachment for wet cutting, Hose whips w/ Flush-Face fittings and Trigger Lockout. (Hydraulic requirements: 8 gpm @ 2000-2500 psi.)

Part #	Description	Weight	Price
2020305	FS20 Hand Saw, Guard and Depth Guide w/ 8 in. cutting depth. 1830 rpm @ 8 gpm	57 lbs.	
2020201	FS20 Hand Saw, Guard, Depth Guide and Upright Handle w/ 8 in. cutting depth. 1830 rpm @ 8 gpm	98 lbs.	
2020203	FS20 Saw and Upright Handle w/ 8 in. cutting depth. 1830 rpm @ 8 gpm	83 lbs.	
2020409	FS20 Upright Handle Kit	41 lbs.	

## FS20 FLAT SAW BLADES

Part #	Description	Price
<b>Arix™ Blades</b>		
5252001	20 in. x .125 in. - with Heavy Rebar	
5252002	20 in. x .125 in. - with Standard Rebar	
<b>Non-Arix™ Blades</b>		
5212211	21 in. x .125 in. - Abrasive without Rebar	
5212212	21 in. x .125 in. - Med-soft, very-Hard with Rebar	
5212213	21 in. x .145 in. - Abrasive without Rebar	
5212214	21 in. x .145 in. - Med-soft, very-Hard with Rebar	

## HYDRACARTS

Part #	Description	Weight	Price
2000483	HydraCart with Ballast Box for slab sawing. (Accommodates 14 in., 16 in., 20 in. and 24 in. HydraSaws)	260 lbs.	
2000489	SawCart for light duty straight line cutting. (Accommodates 14 in. and 16 in. HydraSaws)	74 lbs.	



**HV1658 HydraPak**



**HH2010 HydraPak**



**HV1855 Dual-Output HydraPak**



**HE1010 Electric HydraPak**

**CONTACT RGC FOR OTHER  
 HYDRAPAK OPTIONS INCLUDING  
 BI-DIRECTIONAL HYDRAPAKS AT  
 1-800-RGC-TOOLS**

**HYDRAPAKS WITH GAS ENGINES**

Standard features for RGC HydraPaks with gas engines include electric start, 6 gallon hydraulic reservoir, lifting eye, low oil shutdown and a heavy-duty heat exchanger. Each unit is mounted on a portable cart with 16 in. pneumatic tires.

Part #	Model	Description	Dry Weight	Price
2512161	HV1658	16 hp B&S Vanguard with 5 or 8 gpm output @ 2250 psi w/ hour meter.	226 lbs.	
2514408	HV1858	18 hp B&S Vanguard with 5 or 8 gpm output @ 2250 psi; w/ electronic governor & hour meter.	240 lbs.	
2542010	HH2010	20 hp Honda with 0 - 10 gpm output & three pressure settings (1750, 2000 & 2500 psi); w/ pressure gauge, hour meter & volt meter.	285 lbs.	
2512236	HH2210	22 hp Honda with 0-10 gpm output & three pressure settings (2000, 2500 & 3000 psi); w/ pressure gauge, hour meter & volt meter.	360 lbs.	
2512234	HH2212	22 hp Honda with 0-12 gpm output & three pressure settings (1750, 2000 & 2500 psi); w/ pressure gauge, hour meter & volt meter.	360 lbs.	
2512230	HV2310	23 hp B&S Vanguard with 0 - 10 gpm output & three pressure settings (2000, 2500 & 3400 psi); w/ pressure gauge, hour meter & volt meter.	280 lbs.	
2512232	HV2312	23 hp B&S Vanguard with 0 - 12 gpm output & three pressure settings (1750, 2000 & 2500 psi); w/ pressure gauge, hour meter & volt meter.	280 lbs.	

**DUAL-OUTPUT HYDRAPAKS WITH B & S ENGINES**

The HV1855 and HV185510 have all the standard features of other HydraPaks with Briggs & Stratton gas engines. The advantage is their ability to operate two tools simultaneously. Run a HydraSaw from one circuit while operating a breaker from the other circuit.

Part #	Model	Description	Dry Weight	Price
2514412	HV1855	18 hp B&S Vanguard operates two tools at 5 gpm simultaneously; with electronic governor & hour meter.	251 lbs.	
2514406	HV185510	18 hp B&S Vanguard operates two tools at 5 gpm simultaneously; or one tool at 10 gpm; with electronic governor & hour meter.	251 lbs.	
2535201	HV351212	35 hp B&S Vanguard operates two tools at 12 gpm simultaneously; w/ electronic governor & hour meter.	NA	

**HYDRAPAKS WITH ELECTRIC MOTORS**

RGC electric powered HydraPaks are equipped with an electric motor, 6 gallon reservoir, heavy-duty heat exchanger and lifting eye. Each unit is mounted on a portable cart with 16 in. pneumatic tires.

Part #	Model	Description	Dry Weight	Price
2578102	HE1058	10 hp, 3 ph, 208-230 V, 60 hz electric motor with 5 or 8 gpm output @ 2250 psi; with hour meter. Does not include motor starting or switching equipment.	221 lbs.	
2578135	HE1058	Same as 2578102 with motor starter.	232 lbs.	
2578138	HE1058	Same as 2578102 with 460V & motor starter.	250 lbs.	
2578136	HE1010	10 hp, 3 ph, 208-230 V, 60 hz electric motor with 0 - 10 gpm output and three pressure settings (1750, 2000 & 2500 psi). Includes motor starter, pressure gauge, hour meter, volt meter & deluxe wide tires.	260 lbs.	
2578137	HE1010	Same as 2578136 with 460V.	290 lbs.	
2578140	HE1512	15 hp, 3 ph, 208-230 V, 60 hz electric motor with 0 - 12 gpm output and three pressure settings (1750, 2000 psi continuous duty & 2500 psi intermittent duty only). Includes motor starter, pressure gauge, hour meter, volt meter & deluxe wide tires.	280 lbs.	
2578142	HE1512	Same as 2578140 with 460V.	310 lbs.	

**RGC IS THE  
 NORTH AMERICAN MASTER DISTRIBUTOR  
 FOR HYCON HYDRAULIC TOOLS!**

HYCON HYDRAULIC POWER PACK				
Standard features for Hycon Hydraulic Power Packs include a 2 gallon hydraulic reservoir, lifting eye, low oil shutdown and a very efficient cooling system. Each unit is mounted on a portable cart for easy maneuverability on the jobsite.				
Part #	Model	Description	Weight	Price
2513090	HPP09	9 hp Honda gas engine with 5 gpm output @ 2200 psi.	150 lbs.	
2513130	HPP13 Flex	13 hp Honda gas engine with 8 gpm output @ 2200 psi.	179 lbs.	
2513180	HPP18V Flex	18 hp B&S Vanguard with 10 gpm output @ 2300 psi; w/electric and pull start.	232 lbs.	
2513181	HPP18V Flex XL	18 hp B&S Vanguard with 10 gpm output @ 2300 psi; w/pressure gauge, hour meter, volt meter, electric & pull start. Flat-Free tires are standard.	243 lbs.	

**NOW OFFERING AN 11 HP DIESEL POWER PACK!**

HYCON HYDRAULIC DIESEL POWER PACK				
Part #	Model	Description	Weight	Price
2513132	HPP13D	11 hp Lombardini diesel engine w/ 8 gpm output @ 2000 psi.	179 lbs.	



HPP18V Flex Power Pack



HPP09 Power Pack & Breaker



HPP13 Flex Power Pack



**HH1ORV Hydraulic Breaker**



**HH23-30 Hydraulic Breaker**



**HPD Hydraulic Post Driver**

**HYCON HYDRAULIC BREAKERS**

Hycon Hydraulic Breakers are sold complete with Hose Whips and Moil Points.

Part #	Model	Weight Class	Description	Weight	Price
1813406	HH1ORV	20 lbs.	Hydraulic Breaker. Requires 5 gpm @ 2300 psi. Use with .580 x 2-1/2 in. Tool Steel.	22 lbs.	
1813415	HH15	30 lbs.	Hydraulic Breaker. Requires 5 gpm @ 2300 psi. Use with 7/8 x 3-1/4 in. Tool Steel.	33 lbs.	
1813520	HH20-20	40 lbs.	Hydraulic Breaker. Requires 5 gpm @ 2300 psi. Use with 1 x 4-1/4 in. Tool Steel.	50 lbs.	
1813521	HH21-20	40 lbs.	Hydraulic Breaker. Requires 5 gpm @ 2300 psi. Use with 1-1/8 x 6 in. Tool Steel.	54 lbs.	
1813522	HH22-20	40 lbs.	Hydraulic Breaker. Requires 5 gpm @ 2300 psi. Use with 1-1/4 x 6 in. Tool Steel.	54 lbs.	
1813523	HH23-30	50 lbs.	Hydraulic Breaker. Requires 8 gpm @ 2300 psi. Use with 1x 4-1/4 in. Tool Steel.	53 lbs.	
1813524	HH24-30	50 lbs.	Hydraulic Breaker. Requires 8 gpm @ 2300 psi. Use with 1-1/8 x 6 in. Tool Steel.	57 lbs.	
1813525	HH25-30	50 lbs.	Hydraulic Breaker. Requires 8 gpm @ 2300 psi. Use with 1-1/4 x 6 in. Tool Steel.	57 lbs.	
1813526	HH26-30	70 lbs.	Hydraulic Breaker. Requires 8 gpm @ 2300 psi. Use with 1-1/8 x 6 in. Tool Steel.	61 lbs.	
1813527	HH27-30	70 lbs.	Hydraulic Breaker. Requires 8 gpm @ 2300 psi. Use with 1-1/4 x 6 in. Tool Steel.	61 lbs.	
1813531	HH35	90 lbs.	Hydraulic Breaker. Requires 10 gpm @ 2300 psi. Use with 1-1/4 x 6 in. Tool Steel.	74 lbs.	

Call RGC for availability and pricing on other size breakers. 1-800-RGC-TOOL

**HYCON HYDRAULIC POST DRIVER**

Hycon Hydraulic Post Drivers are sold complete with a remote valve and Hose Whips.

Part #	Model	Description	Impacts/Minute	Weight	Price
2413065	HPD	Hydraulic Post Driver. Requirements are 5 or 8 gpm @ 2300 psi.	1380	65 lbs.	
2413212		2-1/2 in. Square Adaptor			
2413300		3 in. Round Adaptor			

**HYCON HYDRAULIC ROCK DRILL**

The Hycon Hydraulic Rock Drill uses standard ISO or spiral drills and is equipped with a built-in air compressor for air flushing. Additional air supply required for holes deeper than 31-1/2 in. @ 1-3/4 in. diameter. Hose Whips included.

Part #	Model	Description	Impacts/Minute	Weight	Price
1813622	HHRD20	Rock Drill requires 8 gpm @ 2000 psi.	1500 @ 0 rpm – 900 @ 400 rpm	44 lbs.	

# 2017 HYCON HYDRAULIC RING SAW, HAND CORE DRILLS, EARTH DRILL & FLOW DIVIDER



## HYCON HYDRAULIC RING SAW

The HHRS Ring Saw makes it possible to cut up to 11-3/4 in. with only a 15-3/4 in. blade resulting in reduced consumables costs! Cut concrete, block, brick, stone, etc. with or without rebar, indoors, outdoors and even underwater!

Part #	Model	Description	Weight	Price
2016020	HHRS	Requires 8 - 10 gpm @ 2300 psi.	24 lbs.	
<b>Arix™ Rings</b>				
5254161		16 in. 3-Groove Hycon Ring w/ Drive Wheel		
<b>Non-Arix™ Rings</b>				
5213040		16 in. 3-Groove Hycon Ring w/ Drive Wheel - Hard/Rebar		
5213060		16 in. 3-Groove Hycon Ring w/ Drive Wheel - Soft/no Rebar		



HHRS Ring Saw

## HYCON HYDRAULIC HAND CORE DRILLS

Part #	Model	Description	Weight	Price
1712104	HHCD104	Hand-held hydraulic core drill for 1 - 4 in. drill bits (1-1/4 in. UNC thread). Has variable speed control. Hose whips included. Maximum 1500 rpm @ 5 gpm and 2400 rpm @ 8 gpm. Requires 5-8 gpm @ 1500-2500 psi.	17 lbs.	
1712214	HHCD214	Hand-held hydraulic core drill for 2 - 14 in. drill bits (1-1/4 in. UNC thread). Has variable speed control. Hose whips included. Maximum 600 rpm @ 5 gpm and 950 rpm @ 8 gpm. Requires 5-8 gpm @ 1500-2500 psi.	17 lbs.	
1795020		Adapter 1/2 in. - 5/8 in.		
1740020		M-4 Stand		



HHCD214 Hand Core Drill

## HYCON HYDRAULIC EARTH DRILL

The HED earth drill is used for drilling holes for fencing, sign posts, masts and planting jobs. It provides forward and reverse rotation and has a built in torque limiter that stops the tool immediately if the auger gets stuck.

Part #	Model	Description	Weight	Price
2313020	HED	The hydraulic requirements are 5 - 10 gpm @ 1200 psi.	43 lbs.	
2313354		3-1/2 in. bit		
2313591		6 in. bit		
2313197		20 in. extension		



HED Hydraulic Earth Drill

## HYCON HYDRAULIC FLOW DIVIDER

Part #	Model	Description	Price
1613075	HFD	Flow Divider with Hose whips and Flush-Face Fittings. Specify required output of 5, 8 or 10 gpm. Maximum input of 21 gpm & 3500 psi.	



Hydraulic Flow Divider

**2" Water Pump**



**3" Trash Pump**

HYDRAULIC WATER & TRASH PUMPS AND HOSES				
Part #	Model	Description	Weight	Price
2102010	PW200	2" Submersible Water Pump - Max. 250 gpm capacity & 145' lift height. (Requires 5-8 gpm @ 1200-2000 psi.)	16 lbs.	
2127525	PW250	2-1/2" Submersible Water Pump - Max. 275 gpm capacity & 145' lift height. (Requires 4-8 gpm @ 2000 psi.)	12 lbs.	
2150030	PW300	3" Submersible Water Pump - Max. 500 gpm capacity & 120' lift height. (Requires 7-11 gpm @ 2000 psi.)	21 lbs.	
2103008	PT300	3" Submersible Trash Pump - Max. 475 gpm capacity & 100' lift height. (Requires 6-10 gpm @ 1500-2000 psi.)	38 lbs.	
2187540	PT400	4" Submersible Trash Pump - Max. 875 gpm capacity & 45' lift height. (Requires 7-9 gpm @ 2000 psi.)	59 lbs.	
2100221		2" Hose x 25' Long w/ Cam-Lock Fittings		
2100311		3" Hose x 25' Long w/ Cam-Lock Fittings		



**CD616 Hydraulic Core Drill**

HYDRAULIC CORE DRILLS				
Part #	Model	Description	Weight	Price
1715007	CD616	Hydraulic Core Drill for 6 in. to 16 in. drill bits (1-1/4 in. UNC thread). Has variable speed control. Hose whips and M2 Drill Stand with 42 in. mast and spacers with bolts included. Max. 330 rpm @ 8 gpm. (Requires 8 - 15 gpm @ 2000-2500 psi)	158 lbs.	
1715008	CD1824*	Hydraulic Core Drill for 18 in. to 24 in. drill bits (1-1/4 in. UNC thread). Has variable speed control. Hose whips and M2 Drill Stand with 42 in. mast and spacers with bolts included. Max. 200 rpm @ 8 gpm. (Requires 8 - 15 gpm @ 2000 - 2500 psi)	163 lbs.	

\* Unit will accept up to 27 in. tall core bits.  
 Taller masts are available to fit longer core bits.



**Hydraulic Extension Hoses**

HYDRAULIC HOSES			
Part #	Description	Weight	Price
1649116	1/2 in. x 25 ft. pair Extension Hoses with Flush-Face Fittings.	21 lbs.	
1649117	1/2 in. x 50 ft. pair Extension Hoses with Flush-Face Fittings.	38 lbs.	
1649108	1/2 in. x 25 ft. Extension hoses with 3/4 in. Return Line, both with Flush-Face Fittings.	35 lbs.	
1601180	Pair of 1/2 x 12 in. Hose Whips (for Drills, Impact Wrenches, Pole Saws & Hand Chain Saws).	2 lbs.	
1605621	1/2 x 12 in. Hose Whips (for Pole Tampers).	2 lbs.	
6316475	Biodegradable Oil - per gallon.	9 lbs.	

**HYDRAULIC HAND CHAIN SAWS \*\***

Hydraulic requirements are 4 - 8 gpm at 1000 - 2000 psi.

Part #	Model	Overall Length	Cutting Depth	Weight	Price
2309003	APG13	26.5 in.	13 in.	8.5 lbs.	
2309006	AG16	31.5 in.	16 in.	9.5 lbs.	
2309009	AG20	35.5 in.	20 in.	10.2 lbs.	

\* Hose whips not included.

# Longer lead times may apply



**16" Hand Chain Saw**



**13" Adjustable Pistol Grip Hand Chain Saw**

**HYDRAULIC IMPACT WRENCHES AND DRILL \*\***

Part #	Description	Weight	Price
2308029	Impact Wrench - 7/16 in. Hex Head Quick-Change Chuck. 400 ft-lb torque @ 8 gpm. (Requires 4 - 10 gpm @ 1000 - 2500 psi)	7.4 lbs.	
2308030	Impact Wrench - 7/16 in. Hex Head Quick-Change Chuck w/ adjustable torque settings from 80 - 400 ft-lb. (Requires 4 - 12 gpm @ 1000 - 2500 psi)	7.7 lbs.	
2308035	Impact Wrench - 3/4 in. Square Head 1,060 ft-lb torque @ 6 gpm (Requires 4 - 12 gpm @ 1000 - 2000 psi)	12.3 lbs.	
2304587	Impact Wrench - 1 in. Square Head (Requires 10 gpm @ 2000 psi)	24 lbs.	
2308027	Drill - 1/2 in. Variable Speed & Reversible (Requires 4 - 8 gpm @ 1000 - 2000 psi)	6 lbs.	
2308237	Adapter - 7/16 in. hex to 1/2 in. Square Drive bit		

\* Hose whips not included.

# Longer lead times may apply



**3/4 in. Impact Wrench**



**7/16 in. Adjustable Torque Impact Wrench**



**Pole Chain Saw**

**HYDRAULIC POLE CHAIN SAW \***

Open center. Hydraulic requirements are 5 - 8 gpm at 1000 - 2000 psi.

Part #	Model	Overall Length	Cutting Depth	Weight	Price
2307069	PLCHS90	90 in.	13 in.	9 lbs.	

\* Hose whips not included.



**Pole Hook Pruner**

**HYDRAULIC PRUNER \***

Open center and 2 in. jaw opening.  
 Hydraulic requirements are 3 - 6 gpm at 1500 - 2000 psi.

Part #	Model	Overall Length	Weight	Price
2309012	PLPR86	86 in.	9 lbs.	

\* Hose whips not included.



**Pole Tamper**

**HYDRAULIC POLE TAMPERS \* ‡**

Hydraulic requirements are 3 - 10 gpm at 1000 - 2000 psi.  
 4 - 8 gpm is the optimal flow range.

Part #	Model	On/Off Valve	Overall Length	Shoe Type	Weight	Price
2301621	PT60	Yes	60 in.	Specify	36 lbs.	
2301623	PT72	Yes	72 in.	Specify	37 lbs.	
2301727	Square Shoe	-	-	8 in. Square		
2355897	Kidney Shoe	-	-	Kidney		

\* Hose whips not included.

‡ Longer lead times may apply



400 lb. Pivoting Platform Hoist



(See Page 14)

PRO400 Platform Hoist

### PPH 400 LB. CAPACITY

Part #	Description	Weight	Price
O410148	Pivoting Platform Hoist 400 lb. PRO G 44 ft. w/ 4 hp B & S gas engine.	430 lbs.	
O410156	Pivoting Platform Hoist 400 lb. PRO HG 44 ft. w/ 4 hp Honda gas engine.	436 lbs.	
O410140	Pivoting Platform Hoist 400 lb. PRO E 44 ft. w/ 1-1/2 hp electric motor.	457 lbs.	
O410164	Pivoting Track & Platform	81 lbs.	
O410224	Pivoting Platform Hoist Track Roof Support	15 lbs.	
O410236	Pivoting Platform Hoist Truss Carrier	9 lbs.	

### PPH HOIST SOLAR PANEL CARRIER

Part #	Description	Weight	Price
O446160	PPH Solar Panel Carrier Attachment*	31 lbs.	

\* Fits Pivoting Platform Hoist only.

### HANDIHOIST 400 LB. CAPACITY

Part #	Description	Weight	Price
O409412	Handi Hoist w/ 12 ft. track	110 lbs.	
O409416	Handi Hoist w/ 16 ft. track	113 lbs.	
O409428	Handi Hoist w/ 28 ft. track	146 lbs.	
O409444	Handi Hoist w/ 44 ft. track	185 lbs.	

### HANDIHOIST 200 LB. CAPACITY

Part #	Description	Weight	Price
O409212	Handi Hoist w/ 12 ft. track	104 lbs.	
O409216	Handi Hoist w/ 16 ft.	110 lbs.	
O409228	Handi Hoist w/ 28 ft. track	140 lbs.	
O409244	Handi Hoist w/ 44 ft. track	176 lbs.	

### HANDIHOIST ACCESORIES

Part #	Description	Weight	Price
O409510	HandiHoist Winch Assembly w/ Handwheel	70 lb.	
O400540	Telescope Support. Required when lifting to heights over 28 ft.	52 lbs.	
O400557	400 lb. 6 ft. Roller Angle Guide.	43 lbs.	
O400561	400 lb. Plywood Carrier - 5 in. Lifts plywood windows, doors and framing materials.	10 lbs.	
O400562	400 lb. Truss Carrier - 7 in. Lifts roof trusses, framing materials and solar panels.	11 lbs.	
O420403	400 lb. Track Cross Tie Stiffener	1 lb.	
O406042	PL/PRO Cross Tie Repair Kit	5 lbs.	
O403250	200 lb. Plywood Carrier - 5 in. Lifts plywood, windows, doors and framing materials.	13 lbs.	
O403270	200 lb. Truss Carrier - 7 in. Lifts roof trusses, framing materials and solar panels.	13 lbs.	
O420404	200 lb. Track Cross Tie Stiffener	1 lb.	

### PPH FEATURES & BENEFITS

RGC's versatile PPH, Pivoting Platform Hoist, is offered as a 400 lb. capacity, 44 ft. hoist with a choice of PRO drives. Select a 4 hp Briggs & Stratton engine, a 4 hp Honda engine or a 1-1/2 hp electric motor to power your hoist.

The PPH's newly designed pivoting track section is adjustable from 35° to 75° for use on virtually any roof slope. It moves materials to workers farther up the roof and away from the roof's edge. This improves worker safety and increases productivity.

The PPH functions like a conveyor - but without the cost!

### PPH & HANDIHOIST TRACK

Replacement Track Sections and top brackets are the same as those used on standard PRO and Classic Platform Hoists.



Solar Panel Attachment

### HANDIHOIST FEATURES & BENEFITS

Rugged RGC HandiHoists are the dependable, economical and safe environmentally friendly choice for your lifting requirements. Its steel frame provides exceptional durability and easily mounts to RGC track with two lock pins.

The highly portable HandiHoist fits 200 lb. or 400 lb. capacity track. The HandiHoist winch has a 3.5:1 gear ratio and is equipped with a friction disc brake for greater operator control.

HandiHoists are ideal for commercial or residential roofing, HVAC and construction jobs. The new Solar Panel Attachment is the perfect accessory for this hoist!

**PHOTO ON  
 PAGE 12**

<b>PRO PLATFORM HOIST (200 LB. CAPACITY)</b>			
Part #	Description	Weight	Price
O456810	Platform Hoist 200 PRO G 12 ft. w/ 4 hp B & S gas engine	243 lbs.	
O456811	Platform Hoist 200 PRO HG 12 ft. w/ 4 hp Honda gas engine	249 lbs.	
O456809	Platform Hoist 200 PRO E 12 ft. w/ 1-1/2 hp electric motor	270 lbs.	
O456800	Platform Hoist 200 PRO G 16 ft. w/ 4 hp B & S gas engine	252 lbs.	
O456804	Platform Hoist 200 PRO HG 16 ft. w/ 4 hp Honda gas engine	258 lbs.	
O456803	Platform Hoist 200 PRO E 16 ft. w/ 1-1/2 hp electric motor	279 lbs.	
O456801	Platform Hoist 200 PRO G 28 ft. w/ 4 hp B & S gas engine	282 lbs.	
O456806	Platform Hoist 200 PRO HG 28 ft. w/ 4 hp Honda gas engine	288 lbs.	
O456805	Platform Hoist 200 PRO E 28 ft. w/ 1-1/2 hp electric motor	309 lbs.	
O456802	Platform Hoist 200 PRO G 44 ft. w/ 4 hp B & S gas engine	370 lbs.	
O456808	Platform Hoist 200 PRO HG 44 ft. w/ 4 hp Honda gas engine	376 lbs.	
O456807	Platform Hoist 200 PRO E 44 ft. w/ 1-1/2 hp electric motor	397 lbs.	

<b>CLASSIC 200 LB. PLATFORM HOIST</b>			
Part #	Description	Weight	Price
O431212	Platform Hoist 200 Classic G 12 ft. w/ 4 hp B & S gas engine	213 lbs.	
O450922	Platform Hoist 200 Classic HG 12 ft. w/ 4 hp Honda gas engine	220 lbs.	
O431112	Platform Hoist 200 Classic E 12 ft. w/ 1-1/2 hp electric motor	239 lbs.	
O431216	Platform Hoist 200 Classic G 16 ft. w/ 4 hp B & S gas engine	221 lbs.	
O450923	Platform Hoist 200 Classic HG 16 ft. w/ 4 hp Honda gas engine	228 lbs.	
O431116	Platform Hoist 200 Classic E 16 ft. w/ 1-1/2 hp electric motor	247 lbs.	
O431228	Platform Hoist 200 Classic G 28 ft. w/ 4 hp B & S gas engine	251 lbs.	
O450924	Platform Hoist 200 Classic HG 28 ft. w/ 4 hp Honda gas engine	258 lbs.	
O431128	Platform Hoist 200 Classic E 28 ft. w/ 1-1/2 hp electric motor	277 lbs.	
O431244	Platform Hoist 200 Classic G 44 ft. w/ 4 hp B & S gas engine	339 lbs.	
O450925	Platform Hoist 200 Classic HG 44 ft. w/ 4 hp Honda gas engine	346 lbs.	
O431144	Platform Hoist 200 Classic E 44 ft. w/ 1-1/2 hp electric motor	365 lbs.	

<b>200 LB. HOIST SOLAR PANEL CARRIER</b>			
Part #	Description	Weight	Price
O424022	200 lb. Solar Panel Carrier w/ Frame & Top Sheave w/ Bracket Assembly	60 lbs.	
O424030	Solar Panel Carrier Attachment*	25 lbs.	

\* Fits on existing 200 lb. & 400 lb. Platforms.  
 Consult factory for use on the Pivoting Platform Hoist.

<b>200 LB. HOIST ACCESSORIES</b>			
Part #	Description	Weight	Price
O400540	Telescope Support. Required for extra support when lifting to heights over 28 ft.	52 lbs.	
O400019	Scaffolding Support Arm. Allows track to be mounted sideways with support arms at various points along a scaffold frame for safe, sure loading.	24 lbs.	
O403250	200 lb. Plywood Carrier - 5 in. Lifts plywood, windows, doors and framing materials.	13 lbs.	
O403270	200 lb. Truss Carrier. Lifts roof trusses, framing materials and solar panels.	13 lbs.	
O406042	PL/PRO Cross Tie Repair Kit	5 lbs.	
O420404	200 lb. Track Cross Tie Stiffener	1 lb.	

<b>200 LB. PLATFORM &amp; TOP SHEAVE/BACKET</b>			
Part #	Description	Weight	Price
O403225	200 lb. Platform & Top Sheave w/ Bracket Assembly	51 lbs.	
O403226	200 lb. Platform Assembly Only	40 lbs.	
O401100	200 lb. Top Sheave w/ Bracket Assembly Only	12 lbs.	

<b>200 LB. HOIST TRACK SECTIONS</b>			
Part #	Description	Weight	Price
O405570	200 lb. 16 ft. Track w/ Safety Shoes	40 lbs.	
O400571	200 lb. 16 ft. Track w/ Splice Plates	36 lbs.	
O420088	200 lb. 8 ft. Track w/ Safety Shoes	23 lbs.	
O400572	200 lb. 8 ft. Track w/ Splice Plates	19 lbs.	
O400573	200 lb. 4 ft. Track w/ Splice Plates	11 lbs.	

<b>PLATFORM HOIST POWER DRIVES</b>			
Part #	Description	Weight	Price
O402006	PRO Drive w/ 4 hp B & S Gas Engine	158 lbs.	
O402007	PRO Drive w/ 4 hp Honda Gas Engine	164 lbs.	
O402005	PRO Drive w/ 1-1/2 hp Electric Motor	185 lbs.	
O413041	Classic Drive w/ 4 hp B & S Gas Engine	128 lbs.	
O413042	Classic Drive w/ 4 hp Honda Gas Engine	135 lbs.	
O432504	Classic Drive w/ 1-1/2 hp Electric Motor	154 lbs.	

**PHOTO ON PAGE 12**

## PRO PLATFORM HOIST (400 LB. CAPACITY)

Part #	Description	Weight	Price
O455010	Platform Hoist 400 PRO G 12 ft. w/ 4 hp B & S gas engine	278 lbs.	
O455011	Platform Hoist 400 PRO HG 12 ft. w/ 4 hp Honda gas engine	284 lbs.	
O455009	Platform Hoist 400 PRO E 12 ft. w/ 1-1/2 hp electric motor	305 lbs.	
O455000	Platform Hoist 400 PRO G 16 ft. w/ 4 hp B & S gas engine	284 lbs.	
O455004	Platform Hoist 400 PRO HG 16 ft. w/ 4 hp Honda gas engine	290 lbs.	
O455003	Platform Hoist 400 PRO E 16 ft. w/ 1-1/2 hp electric motor	311 lbs.	
O455001	Platform Hoist 400 PRO G 28 ft. w/ 4 hp B & S gas engine	317 lbs.	
O455006	Platform Hoist 400 PRO HG 28 ft. w/ 4 hp Honda gas engine	323 lbs.	
O455005	Platform Hoist 400 PRO E 28 ft. w/ 1-1/2 hp electric motor	344 lbs.	
O455002	Platform Hoist 400 PRO G 44 ft. w/ 4 hp B & S gas engine	408 lbs.	
O455008	Platform Hoist 400 PRO HG 44 ft. w/ 4 hp Honda gas engine	414 lbs.	
O455007	Platform Hoist 400 PRO E 44 ft. w/ 1-1/2 hp electric motor	435 lbs.	

## CLASSIC 400 LB. PLATFORM HOIST

Part #	Description	Weight	Price
O431412	Platform Hoist 400 Classic G 12 ft. w/ 4 hp B & S gas engine	248 lbs.	
O450943	Platform Hoist 400 Classic HG 12 ft. w/ 4 hp Honda gas engine	255 lbs.	
O431312	Platform Hoist 400 Classic E 12 ft. w/ 1-1/2 hp electric motor	274 lbs.	
O431416	Platform Hoist 400 Classic G 16 ft. w/ 4 hp B & S gas engine	263 lbs.	
O450944	Platform Hoist 400 Classic HG 16 ft. w/ 4 hp Honda gas engine	363 lbs.	
O431316	Platform Hoist 400 Classic E 16 ft. w/ 1-1/2 hp electric motor	282 lbs.	
O431428	Platform Hoist 400 Classic G 28 ft. w/ 4 hp B & S gas engine	289 lbs.	
O450945	Platform Hoist 400 Classic HG 28 ft. w/ 4 hp Honda gas engine	296 lbs.	
O431328	Platform Hoist 400 Classic E 28 ft. w/ 1-1/2 hp electric motor	315 lbs.	
O431444	Platform Hoist 400 Classic G 44 ft. w/ 4 hp B & S gas engine	380 lbs.	
O450946	Platform Hoist 400 Classic HG 44 ft. w/ 4 hp Honda gas engine	387 lbs.	
O431344	Platform Hoist 400 Classic E 44 ft. w/ 1-1/2 hp electric motor	406 lbs.	

## 400 LB. HOIST SOLAR PANEL CARRIER

Part #	Description	Weight	Price
O444044	400 lb. Solar Panel Carrier w/ Frame & Top Sheave w/ Bracket Assembly	83 lbs.	
O424030	Solar Panel Carrier Attachment*	25 lbs.	

\* Fits on existing 200 lb. & 400 lb. Platforms. Consult factory for use on the Pivoting Platform Hoist.

## PLATFORM HOIST SPECIFICATIONS

	400	200
Load Capacity	400 lbs.	200 lbs.
Lift Speed	110 fpm	220 fpm
Platform Size	24 in. x 24 in.	17 in. x 18 in.
Track (3-3/4 in. Side Rail)	24 in. wide	17 in. wide

## 400 LB. HOIST ACCESSORIES

Part #	Description	Weight	Price
O400557	400 lb. 6 ft. Roller Angle Guide. Moves material away from roof edge on shallow inclines.	43 lbs.	
O400558	400 lb. Gravel Hopper. Lifts granular materials and discharges load into wheel barrows, spreaders and other containers.	52 lbs.	
O400561	Plywood Carrier - 5 in. Lifts plywood, wallboard, windows, doors and framing materials.	10 lbs.	
O400562	Truss Carrier - 7 in. Lifts roof trusses, framing materials and solar panels.	11 lbs.	
O400540	Telescope Support. Required for extra support when lifting to heights over 28 ft.	52 lbs.	
O400019	Scaffolding Support Arm. Allows track to be mounted sideways with support arms at various points along a scaffold frame for safe, sure loading.	24 lbs.	
O406042	PL/PRO Cross Tie Repair Kit	5 lbs.	
O420403	400 lb. Track Cross Tie Stiffener	1 lb.	

## 400 LB. PLATFORM & TOP SHEAVE/BACKET

Part #	Description	Weight	Price
O405667	400 lb. Platform & Top Sheave w/ Bracket Assembly	83 lbs.	
O401400	400 lb. Platform Assembly Only	69 lbs.	
O400567	400 lb. Top Sheave w/ Bracket Assembly Only	15 lbs.	

## 400 LB. HOIST TRACK SECTIONS

Part #	Description	Weight	Price
O405552	400 lb. 16 ft. Track w/ Safety Shoes	43 lbs.	
O400553	400 lb. 16 ft. Track w/ S	39 lbs.	
O440088	400 lb. 8 ft. Track w/ Safety Shoes	25 lbs.	
O400554	400 lb. 8 ft. Track w/ Splice Plates	21 lbs.	
O400555	400 lb. 4 ft. Track w/ Splice Plates	12 lbs.	

# **RGC**<sup>®</sup>

**REIMANN & GEORGER CORP.**  
**HOISTING - MARINE - CONSTRUCTION**

CAGE Code #51097



**C100 HYDRACUTTER**  
**— Available Spring 2017 —**

**REIMANN & GEORGER CORPORATION**  
1849 Harlem Road • Buffalo, NY 14212

**1-800-RGC-TOOLS (742-8665)**  
**FAX: 1-716-895-1547**

*View our entire line of Construction,  
Hoisting and Marine equipment at*

**[www.rgcproducts.com](http://www.rgcproducts.com)**  
**[sales@rgcproducts.com](mailto:sales@rgcproducts.com)**



Distributed by:



Prices and products subject to change without notice. Freight F.O.B. Buffalo, NY.